

GHS **SAFETY DATA SHEET**

I. PRODUCT IDENTIFICATION

MANUFACTURER/SUPPLIER CHEMICAL/TRADE NAME Lead Oxide

Exide Technologies (as used on label)

13000 Deerfield Parkway, Bldg. 200 Milton, GA 30004 PRODUCT ID UN3077

FOR FURTHER INFORMATION CHEMICAL FAMILY/ Litharge, leady oxide, lead monoxide, leady lead oxide

Primary Contact: CLASSIFICATION

Exide SDS Support (770) 421-3485 FOR EMERGENCY Secondary Contact:

Joe Bolea (423) 989-6377 CHEMTREC (800) 424-9300 (703) 527-3887 - Collect

Fred Ganster (610) 921-4052 24-hour Emergency Response Contact Ask for Environmental Coordinator

II. HAZARD IDENTIFICATION





Signal Word: Danger

Category:	GHS Codes	Description
	H302	Harmful if swallowed
Health:	H332	Harmful if inhaled
	H360df	May damage fertility or unborn child
Acute Tox 4	H373	May cause damage to the central nervous system and systems for
Repro 1A		reproduction organs through prolonged or repeated exposure.
STOT RE 2	P201	Obtain special instructions before use
	P202	Do not handle until all safety precautions have been read and understood
	P260	Do not breathe dust/vapors
Aquatic Acute 1 Acute Chronic 1	P281	Use personal protective equipment as required
Acute Chronic 1	P308+P313	IF exposed or concerned: get medical advice/attention
	H400	Very toxic to aquatic life
	H410	Very toxic to aquatic life with long lasting effects
	P405	Store locked up
Handling:	P501	Dispose of contents/container in accordance with
-		local/regional/national/international regulation.

WARNING: None

Reactivity: strong oxidizers, hydrogen peroxide, acids

III. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	% by Wt.
Powdered Lead	7439-92-1	0-31
Lead Monoxide	1317-36-8	69-100

IV. FIRST AID MEASURES

Take proper precautions to ensure you own health and safety before attempting to rescue a victim and provide first aid.

Inhalation Remove from exposure, gargle, wash nose and lips; consult physician.

Skin Contact: Wash immediately with brush, with soap and water, flush with plenty of water, contact a physician.

Flush immediately with large amounts of water for at least 15 minutes; consult physician immediately. **Eye Contact:**

Induce vomiting if conscious, wash nose and lips; give a demulcent, consult physician. **Ingestion:**

V. FIRE FIGHTING MEASURES Flash Point: Not Applicable

Flammable Limits: Not Applicable

Extinguishing media: CO₂, foam, or dry chemical. **DO NOT use water (H₂O) when molten metal is present.**

Fire Fighting Procedures:

Use full body protective clothing and full-face piece, positive pressure, self-contained breathing apparatus.

Hazardous Combustion Products:

Molten metals produce fume, vapor and/or dust that may be toxic and/or respiratory irritants. This product, or its dust, can react vigorously with strong oxidizing agents.

VI. ACCIDENTAL RELEASE MEASURES

Lead dust or particulate should be vacuumed (using HEPA filter) or wet-swept. Use controls that minimize fugitive emissions. Do not dry sweep nor use compressed air. Place in dry, closed containers for disposal or recycling.

VII. HANDLING AND STORAGE

Handling:

AVOID SKIN CONTACT.

Storage:

Store in a dry area where accidental contact with acids or strong oxidizers is not possible.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

	Occupational Exposure Limits (mg/m³)					
Ingredient:	US	US	US	Quebec	Ontario	EU
	OSHA	ACGIH	NIOSH	PEV	OEL	OEL
Powdered Lead	0.05	0.05	0.05	0.05	0.05	0.15(a,b)
Lead oxide	0.05(a)	0.05(a)	0.05(a)	0.05(a)	0.05(a)	0.15(a,b)

NOTES:

- (a) as inorganic lead
- (b) as inhalable aerosol

Engineering Controls (Ventilation):

Ventilation, as described in the Industrial Ventilation Manual produced by the American Conference of Governmental Industrial Hygienists, shall be provided in areas where exposures are above the permissible exposure limits or threshold limit values specified by OSHA or other federal, state, or local regulations.

Hygiene Practices:

Wash hands thoroughly before eating, drinking or smoking.

Respiratory Protection (NIOSH/MSHA approved):

As specified by 29 CFR 1910.1025 (f) of the Federal Occupational Safety and Health Administration Standards for Occupational Exposure to lead. Other local and state regulations may also apply. Where exposure is above the permissible exposure limit or the threshold limit values, the minimum respiratory protection recommended is a negative pressure half-mask respirator with high-efficiency cartridges that are NIOSH/MSHA approved against dust, mist, and fumes having a TWA of 0.05 mg/m³.

Skin Protection:

Protective gloves should be worn when handling this product.

Eye Protection:

Safety glasses or goggles should be worn when using this product to prevent particles of dust from getting into the eyes. Whenever working with molten metal, a full face shield is recommended.

Other Protection:

Coveralls or other full body clothing shall be worn during product use and properly laundered after use, with the wash water disposed of in accordance with local, state and federal regulations. Hard hat, safety boots and other safety equipment should be worn as appropriate for the industrial environment. Personal clothing and shoes should be protected from contamination with this product.

IX. PHYSICAL AND CHEMICAL PROPERTIES - LEAD OXIDE				
Boiling Point@760 mm Hg	2700°F	Specific Gravity @ 70°F (H ₂ O=1	1) 9.5	
Melting Point	1630°F	Vapor Pressure (mm Hg)	Not Applicable	
% Solubility in Water	0.0017 g/ml	рН	Not applicable	
Evaporation Rate	Not Applicable	Vapor Density (AIR=1)	Not Applicable	
(Butyl acetate=1)		Viscosity	Not applicable	
Appearance and Odor	Yellow to greenish-brown powder, no apparent odor	% Volatiles by Weight	Not Applicable	
Octanol Water Partition Coefficient (K _{ow})	Not Applicable			

X. STABILITY & REACTIVITY DATA

Stability: Stable \underline{X}

Unstable ___

Conditions to Avoid: None

Incompatibilities: (materials to avoid)

Strong oxidizers and this product may react violently and liberate hydrogen gas.

Hazardous Decomposition Products:

Temperatures above the melting point are likely to produce heavy metal fume, vapor, and/or dust

Hazardous Polymerization: Will Not Occur

XI. TOXICOLOGICAL DATA

Routes of Entry:

Lead compounds are harmful by inhalation, skin contact, ingestion, and eye contact.

Acute Toxicity:

Inhalation LD_{50} : Elemental Lead: Acute Toxicity Point Estimate = 4500 ppmV (based on lead bullion)

Oral LD₅₀: Elemental lead: Acute Toxicity Estimate (ATE) = 500 mg/kg body weight (based on lead bullion)

Inhalation:

Inhalation of lead dust or fumes may cause irritation of upper respiratory tract and lungs and can result in both acute and chronic overexposure.

Ingestion:

Acute ingestion may cause abdominal pain, nausea, vomiting, diarrhea, and severe cramping. This may lead rapidly to systemic toxicity.

Skin Contact:

Dust, vapor, and/or fume may cause irritation. Not a dermal sensitizer.

Eye Contact:

Dust, vapor, and/or fume may cause eye irritation.

Synergistic Products:

<u>Lead compounds</u>: Synergistic effects have been noted with heavy metals (arsenic, cadmium, mercury), N-nitroso-N-(hydroxyethyl)ethylamine, N-(4-fluoro-4-biphenyl)acetamide, 2-(nitrosoethylamine)ethanol, and benzo[a]pyrene

Additional Information:

Medical Conditions Generally Aggravated by Exposure:

Lead and its compounds can aggravate some forms of kidney, liver, and neurologic diseases.

Additional Health Data:

All heavy metals, including the hazardous ingredients in this product, are taken into the body primarily by inhalation and ingestion. Most inhalation problems can be avoided by adequate precautions such as ventilation and respiratory protection covered in Section VIII. Follow good personal hygiene to avoid inhalation and ingestion: wash hands, face, neck and arms thoroughly before eating, smoking or leaving the work site. Keep contaminated clothing out of non-contaminated areas, or wear cover clothing when in such areas. Restrict the use and presence of food, tobacco and cosmetics to non-contaminated areas. Work clothes and work equipment used in contaminated areas must remain in designated areas and never taken home nor laundered with personal non-contaminated clothing.

This product is intended for industrial use only and should be isolated from children and their environment.

XII. ECOLOGICAL INFORMATION

Environmental Fate: lead is very persistent in soil and sediments. No data on environmental degradation. Mobility of metallic lead between ecological compartments is slow. Bioaccumulation of lead occurs in aquatic and terrestrial animals and plants but little bioaccumulation occurs through the food chain. Most studies include lead compounds and not elemental lead.

Environmental Toxicity: Aquatic Toxicity:

Lead: 48 hr LC₅₀ (modeled for aquatic invertebrates): <1 mg/L, based on lead bullion

XIII. DISPOSAL INFORMATION

US

Material should be recycled at a secondary lead smelter. Dispose of toxic substances in accordance with approved local, state, and federal requirements. Consult state environmental agency and/or federal EPA.

XIV. TRANSPORT INFORMATION

GROUND: - US-DOT/CAN-TDG/EU-ADR/APEC-ADR:

Environmentally hazardous substance, solid, n.o.s., (contains lead)

UN 3077, 9, PG III Label: "Class 9"

Reportable Quantity: RQ 10 (4.54) if this hazardous substances is limited to those pieces of the metal having a diameter smaller than 100 micrometers (0.004 inches)

AIRCRAFT – ICAO-IATA:

Environmentally hazardous substance, solid, n.o.s., (contains lead)

UN 3077, 9, PG III

Label: "Miscellaneous"

For air shipments, reference IATA Dangerous Goods Regulations Special Provision A97, A158, A179 and Packing Instruction P956.

VESSEL - IMO-IMDG:

Environmentally hazardous substance, solid, n.o.s., (contains lead)

UN 3077, 9, PG III

For shipments by water, reference IMDG Special Provision 274, 335 and Packing Instruction P002 and LP02 or IBC Instructions IBC08.

Additional Information:

- Transport requires proper packaging and paperwork, including the Nature and Quantity of goods, per applicable origin/destination/customs points as-shipped.

XV. REGULATORY INFORMATION

United States:

CERCLA (Superfund) and EPCRA:

- (a) EPCRA Section 312 Tier Two reporting is required if lead is present in quantities of **10,000 lbs** or more.
- (b) **Supplier Notification:** This product contains toxic chemicals that may be reportable under EPCRA Section 313 Toxic Chemical Release Inventory (Form R) requirements. For a manufacturing facility under SIC codes 20 through 39, the following information is provided to enable you to complete the required reports:

Approximate

<u>Toxic Chemical</u>

Lead and Lead Compounds

Lead Monoxide

Approximate

<u>% by Weight</u>

0-31%

1317-36-8

69-100%

If you distribute this product to other manufacturers in SIC Codes 20 through 39, this information must be provided with the first shipment of each calendar year.

Note: The Section 313 supplier notification requirement does not apply to materials that are "consumer products".

TSCA: Each ingredient chemical listed in Section III of this SDS is also listed on the TSCA Registry.

OSHA: Considered hazardous under Hazard Communication Act (29CFR1910.1200)

RCRA: Lead contaminated material may be regulated as a characteristic hazardous waste EPA hazardous waste number D008. Consult local or state environmental agency and/or federal EPA for guidance.

CAA: Exide Technologies supports preventative actions concerning ozone depletion in the atmosphere due to emissions of CFC's and other ozone depleting chemicals (ODC's), defined by the USEPA as Class I substances. Pursuant to Section 611 of the Clean Air Act Amendments (CAAA) of 1990, finalized on January 19, 1993, Exide established a policy to eliminate the use of Class I ODC's prior to the May 15, 1993 deadline.

Additional Data:

Refer to the latest revision of the OSHA general Industry Standards, 29 CFR 1910. Information about the hazardous ingredients contained in lead compounds is shown in Subpart Z – Toxic and Hazardous Substances, Inorganic Lead Standard 1910.1025.

US State Notifications	Identification	Notifications/Warning	
& Warnings: California	California Proposition	"WARNING: This product contains lead, a chemical known to the State of	
Camorina	65	California to cause cancer, or birth defects or other reproductive harm."	
		The following chemicals identified to exist in the finished product as distributed	
		into commerce are known to the State of California to cause cancer, birth defects	
		or to cause reproductive harm:	
		1. Lead – CAS No. 7439-92-1; 0-31% wt.	
		2. Lead monoxide – CAS No. 1317-36-8; 69-100%	
	Consumer Product	This product is not regulated as a consumer product for purposes of CARB/OTC	
	Volatile Organic	VOC Regulations, as sold for the intended purpose and into the	
Country/Organization	Compound Emissions Identification	industrial/commercial supply chain. Notifications/Warning	
		5	
Canada	All chemical	This product has a WHMIS Classification of D2A.	
	substances in this product are listed on	This product has been classified in accordance with the hazard criteria of the	
	the CEPA DSL/NDSL	Controlled Products Regulations and the MSDS contains all the information	
	or are exempt from list	required by the Controlled Products Regulations.	
	requirements.		
		Refer to the Controlled Products Regulations for product labeling requirements	
	NPRI and Ontario	This product contains the following chemicals subject to the reporting	
	Regulation 127/01	requirements of Canada NPRI and/or Ont. Reg. 127/01:	
		<u>Chemical</u> <u>CAS #</u> <u>%wt</u> Lead 7439-92-1 0-31	
		Lead 7439-92-1 0-31 Lead monoxide 1317-36-8 69-100	
	Toxic Substances List	Lead Holloxide 1317-30-8 09-100	
EU	European Inventory of	All ingredients remaining in the finished product as distributed into commerce are	
LC	Existing Commercial	exempt from, or included on, the European Inventory of Existing Commercial	
	Chemical Substances	Chemical Substances.	
	(EINECS):		
		VI. OTHER INFORMATION	
DATE ISSUED: Septemb	per 11, 2013		
OTHER INFORMATION	N:	Distribution into Quebec to follow Canadian Controlled Product Regulations (CPR)	
		24(1) and 24(2).	
		Distribution into the EU to follow applicable Directives to the Use, Import/Export	
SOURCES OF INFORMATION:		of the product as-sold. International Agency for Research on Cancer (1987), IARC Monographs on the	
		Evaluation of Carcinogenic Risks to Humans: Overall Evaluations of	
		Carcinogenicity: An updating of IARC Monographs Volumes 1-42, Supplement 7,	
		Lyon, France.	
		Ontario Ministry of Labor Regulation 654/86. Regulations Respecting Exposure to	
		Chemical or Biological Agents.	
EXIDE		RONMENTAL, SAFETY AND HEALTH DEPARTMENT	
		E TECHNOLOGIES	
		DEERFIELD PKWY., BLDG. 200	
MILTON, GA 30004			

VENDEE AND THIRD PERSONS ASSUME THE RISK OF INJURY PROXIMATELY CAUSED BY THE MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT FOLLOWED AS PROVIDED FOR IN THE DATA SHEET, AND VENDOR SHALL NOT BE LIABLE FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL EVEN IF REASONABLE PROCEDURES ARE FOLLOWED.

ALL PERSONS USING THIS PRODUCT, ALL PERSONS WORKING IN AN AREA WHERE THIS PRODUCT IS USED, AND ALL PERSONS HANDLING THIS PRODUCT SHOULD BE FAMILIAR WITH THE CONTENTS OF THIS DATA SHEET. THIS INFORMATION SHOULD BE EFFECTIVELY COMMUNICATED TO EMPLOYEES AND OTHERS WHO MIGHT COME IN CONTACT WITH THE PRODUCT.

WHILE THE INFORMATION ACCUMULATED AND SET FORTH HEREIN IS BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF, EXIDE TECHNOLOGIES MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE FOR THEIR PARTICULAR CIRCUMSTANCES.

ANY PHOTOCOPY MUST BE OF THIS ENTIRE DOCUMENT