



# JOHNSEN'S ENGINE DEGREASER 16 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/26/2014

Version:

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : JOHNSEN'S ENGINE DEGREASER 16 OZ.  
Product code : 4644

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Degreaser

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Compressed gas H280  
Skin Irrit. 2 H315  
Eye Irrit. 2B H320

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H280 - Contains gas under pressure; may explode if heated  
H315 - Causes skin irritation  
H320 - Causes eye irritation

Precautionary statements (GHS-US) :

P264 - Wash affected areas thoroughly after handling  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P302+P352 - If on skin: Wash with plenty of soap and water  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P321 - Specific treatment: See section 4.1 on SDS  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362 - Take off contaminated clothing and wash before reuse  
P410+P403 - Protect from sunlight. Store in a well-ventilated place

#### 2.3. Other hazards

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated.

#### 2.4. Unknown acute toxicity (GHS-US)

No data available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Water	(CAS No) 7732-18-5	85 - 95	Not classified
Petroleum Gases, Liquefied, Sweetened	(CAS No) 68476-86-8	1 - 5	Flam. Gas 1, H220 Flam. Liq. 1, H224

# JOHNSEN'S ENGINE DEGREASER 16 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	Classification (GHS-US)
2-Butoxyethanol	(CAS No) 111-76-2	1 - 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Nonlyphenol Ethoxylate	(CAS No) 127087-87-0	< 1	Eye Irrit. 2B, H320
Ammonium Hydroxide, Aqueous Solution, Conc=25%	(CAS No) 1336-21-6	< 1	Skin Corr. 1B, H314 Aquatic Acute 1, H400
Sodium Hydroxide, Conc=50%, Aqueous Solution	(CAS No) 1310-73-2	0.0132 - 0.1236	Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 2, H401
Polyethylene Glycol 200-600	(CAS No) 25322-68-3	<= 0.0288	Not classified
Nonyl Nonoxynol-5	(CAS No) 9014-93-1	<= 0.0192	Not classified
Sodium Chloride	(CAS No) 7647-14-5	0 - 0.012	Not classified

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause irritation or asthma-like symptoms.
- Symptoms/injuries after skin contact : Itching. Red skin. Skin rash/inflammation. Causes skin irritation.
- Symptoms/injuries after eye contact : Irritation of the eye tissue. Redness of the eye tissue. Inflammation/damage of the eye tissue. Causes eye irritation.
- Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : NFPA Aerosol Level 1.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

# JOHNSEN'S ENGINE DEGREASER 16 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
- Methods for cleaning up : Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.
- Storage area : Store in a well-ventilated place.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Petroleum Gases, Liquefied, Sweetened (68476-86-8)		
USA ACGIH	ACGIH TWA (ppm)	1000 ppm Listed under Aliphatic hydrocarbon gases alkane C1-C4
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

2-Butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	97 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA ACGIH	ACGIH STEL (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

### 8.2. Exposure controls

- Appropriate engineering controls : Local exhaust ventilation, vent hoods.
- Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Wear appropriate mask.
- Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Gas
- Appearance : Liquid.

# JOHNSEN'S ENGINE DEGREASER 16 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Color	: Milky.
Odor	: Mild . Characteristic.
Odor threshold	: No data available
pH	: 10
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: -31.1 °C (Lowest Component)
Flash point	: -128.9 °C (Lowest Component)
Auto-ignition temperature	: 237.8 °C (Lowest Component)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.99
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : 7.7 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>2-Butoxyethanol (111-76-2)</b>	
LD50 oral rat	530 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 1746 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg (435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value,435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence
<b>Polyethylene Glycol 200-600 (25322-68-3)</b>	
LD50 oral rat	> 15000 mg/kg (Rat)
LD50 dermal rabbit	> 20000 mg/kg (Rabbit)

# JOHNSEN'S ENGINE DEGREASER 16 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Sodium Chloride (7647-14-5)</b>	
LD50 oral rat	3000 mg/kg (Rat; Experimental value; 3550 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit; Experimental value)
Skin corrosion/irritation	: Causes skin irritation. pH: 10
Serious eye damage/irritation	: Causes eye irritation. pH: 10
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

<b>2-Butoxyethanol (111-76-2)</b>	
IARC group	3
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause irritation or asthma-like symptoms.
Symptoms/injuries after skin contact	: Itching. Red skin. Skin rash/inflammation. Causes skin irritation.
Symptoms/injuries after eye contact	: Irritation of the eye tissue. Redness of the eye tissue. Inflammation/damage of the eye tissue. Causes eye irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>2-Butoxyethanol (111-76-2)</b>	
LC50 fish 1	116 ppm (96 h; Cyprinodon variegatus; Nominal concentration)
EC50 Daphnia 1	1700 mg/l (48 h; Daphnia sp.; Nominal concentration)
LC50 fish 2	1341 ppm (96 h; Lepomis macrochirus)
EC50 Daphnia 2	1720 mg/l (24 h; Daphnia magna)
TLM fish 1	100 - 1000,96 h; Pisces
TLM other aquatic organisms 1	100 - 1000,96 h
Threshold limit algae 1	900 mg/l (168 h; Scenedesmus quadricauda)
Threshold limit algae 2	35 mg/l (192 h; Microcystis aeruginosa)

<b>Polyethylene Glycol 200-600 (25322-68-3)</b>	
LC50 fish 1	> 1000 mg/l (96 h; Pisces)
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)
LC50 fish 2	> 5000 mg/l (24 h; Carassius auratus)
Threshold limit other aquatic organisms 1	<= 100 mg/l (96 h; Plankton)
Threshold limit other aquatic organisms 2	> 1000 mg/l
Threshold limit algae 2	500 mg/l (720 h; Algae; No effect)

<b>Sodium Chloride (7647-14-5)</b>	
LC50 fish 1	11100 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	1000 mg/l (48 h; Daphnia magna)
LC50 fish 2	5840 mg/l (96 h; Lepomis macrochirus)
EC50 Daphnia 2	340.7 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	4967 mg/l (72 h; Algae; Inhibitory)
Threshold limit algae 2	2430 mg/l (120 h; Algae)

### 12.2. Persistence and degradability

<b>JOHNSEN'S ENGINE DEGREASER 16 OZ.</b>	
Persistence and degradability	Not established.

<b>Petroleum Gases, Liquefied, Sweetened (68476-86-8)</b>	
Persistence and degradability	Not established.

# JOHNSEN'S ENGINE DEGREASER 16 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>2-Butoxyethanol (111-76-2)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.20 g O <sub>2</sub> /g substance
ThOD	2.305 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.31 % ThOD

<b>Polyethylene Glycol 200-600 (25322-68-3)</b>	
Persistence and degradability	Biodegradability in water: no data available.

<b>Nonyl Nonoxynol-5 (9014-93-1)</b>	
Persistence and degradability	Not established.

<b>Nonlyphenol Ethoxylate (127087-87-0)</b>	
Persistence and degradability	Not established.

<b>Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the components available. Ozonation in the air.

<b>Water (7732-18-5)</b>	
Persistence and degradability	Not established.

<b>Sodium Hydroxide, Conc=50%, Aqueous Solution (1310-73-2)</b>	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the components available.

<b>Sodium Chloride (7647-14-5)</b>	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

### 12.3. Bioaccumulative potential

<b>JOHNSEN'S ENGINE DEGREASER 16 OZ.</b>	
Bioaccumulative potential	Not established.

<b>Petroleum Gases, Liquefied, Sweetened (68476-86-8)</b>	
Bioaccumulative potential	Not established.

<b>2-Butoxyethanol (111-76-2)</b>	
Log Pow	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>Polyethylene Glycol 200-600 (25322-68-3)</b>	
Log Pow	-1.2
Bioaccumulative potential	Bioaccumulation: not applicable.

<b>Nonyl Nonoxynol-5 (9014-93-1)</b>	
Bioaccumulative potential	Not established.

<b>Nonlyphenol Ethoxylate (127087-87-0)</b>	
Bioaccumulative potential	Not established.

<b>Ammonium Hydroxide, Aqueous Solution, Conc=25% (1336-21-6)</b>	
Bioaccumulative potential	Not bioaccumulative.

<b>Water (7732-18-5)</b>	
Bioaccumulative potential	Not established.

<b>Sodium Hydroxide, Conc=50%, Aqueous Solution (1310-73-2)</b>	
Bioaccumulative potential	Does not contain bioaccumulative component(s).

<b>Sodium Chloride (7647-14-5)</b>	
Log Pow	-3.0 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

<b>2-Butoxyethanol (111-76-2)</b>	
Surface tension	0.027 N/m (25 °C)

# JOHNSEN'S ENGINE DEGREASER 16 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.2, Limited Quantity

ICAO/IATA (air): UN1950, Aerosols, 2.2, Limited Quantity

IMO/IMDG (water): UN1950, Aerosols, 2.2, Limited Quantity

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols  
non-flammable, (each not exceeding 1 L capacity)

Department of Transportation (DOT) Hazard Classes : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

### 14.3. Additional information

Other information : No supplementary information available.

### Overland transport

No additional information available

### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### JOHNSEN'S ENGINE DEGREASER 16 OZ.

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Sudden release of pressure hazard
-------------------------------------	---

#### Petroleum Gases, Liquefied, Sweetened (68476-86-8)

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Sudden release of pressure hazard
-------------------------------------	---

#### Nonlyphenol Ethoxylate (127087-87-0)

Listed on United States SARA Section 313

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard
-------------------------------------	--

# JOHNSEN'S ENGINE DEGREASER 16 OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Nonlyphenol Ethoxylate (127087-87-0)

SARA Section 313 - Emission Reporting 5 % Glycol Ethers

### Sodium Hydroxide, Conc=50%, Aqueous Solution (1310-73-2)

Listed on the United States SARA Section 302

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

## 15.2. International regulations

### CANADA

#### JOHNSEN'S ENGINE DEGREASER 16 OZ.

WHMIS Classification Class A - Compressed Gas

#### Sodium Hydroxide, Conc=50%, Aqueous Solution (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Class E - Corrosive Material

### EU-Regulations

No additional information available

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.1; R45

Muta.Cat.2; R46

F+; R12

Xi; R36/38

Full text of R-phrases: see section 16

### 15.2.2. National regulations

No additional information available

## 15.3. US State regulations

### 2-Butoxyethanol (111-76-2)

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - New Jersey - Right to Know Hazardous Substance List

### Sodium Hydroxide, Conc=50%, Aqueous Solution (1310-73-2)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

Rhode Island Right to Know

## SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Compressed gas	Gases under pressure Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 4	Flammable liquids Category 4



# JOHNSEN'S ENGINE DEGREASER 16 OZ.

## Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H224	Extremely flammable liquid and vapor
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H401	Toxic to aquatic life

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 1 Slight Hazard

Physical : 1 Slight Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*